



STEP 1

Insert the 4 slotted tabs into the 4 slots at the end of the VH-Sport. The 2 holes in the middle of the bracket and the 2 holes in the middle of the main rail should line up. Fasten the chock bracket to the main rail using the included (2) 5/16" x 3/4" Hex Head Pointed Screws. Next, attach the chock to the bracket using the (4) 3/8" x 1" bolts though the for square holes in the top of the chock base plate. These holes should line up with the welded nuts in the sides of the chock bracket. Thank you for purchasing the VH-Chock upgrade for the VH-Sport. For questions or concerns please contact BNK, Inc.

Warning

A warning indicates a potentially hazardous situation which, if not avoided, could result in death or serious injury.

1. Read all instructions and save them for later reference.
2. Follow all warnings and instructions marked on the product.
3. Do not stand on the Versa-Haul.
4. Do not ride any vehicle during loading.
5. Store Versa-Haul carrier in a safe place.
6. Do not exceed vehicle tongue weight rating.
7. Only use with class III hitch. Most class III hitches limit Versa-Haul to 500 lbs. total hauling capacity.
8. Improper use of carrier could result in death or serious injury.
9. Do not put Versahaul onto a 5th wheel trailer or any other kind of trailer.
10. **VH-Sport carrying capacity is limited to 600 lbs. max. Your vehicle suspension and hitch may limit the hauling capacity of the carrier.** For more information on vehicles and hauling capacities, visit www.versahaul.com

Manufacturer Information

Manufacturer's Name: BNK, Inc.

Manufacturer's Address:

BNK, Inc.
9341 S. St. Rd. 39
Winamac, IN 46996
(574) 278-7149

Product Name: Versa-Haul VH-Chock

Product Description: Motorcycle Chock Upgrade for VH-Sport

Model Number(s): VH-Chock for VH-Sport

Patent Number:

Serial number _____

(please fill in serial number affixed to Versa-Haul)